

Product data sheet

Specifications



Rack PDU, Switched, 1U, 16A, 208/230V, (8)C13



AP7921

! Discontinued on: 29 March 2023

! To be end-of-service on: 28 June 2023

! Discontinued - Service only

Overview

Lead time Usually in Stock

Main

Main Input Voltage	200 V 208 V 230 V
PDU Type	Switched
Main Output Voltage	208 V 230 V
Input Connection Type	IEC 60320 C20
Number of rack unit	1U
Cable length	8.2 ft (2.50 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets User Manual

Physical

Color	Black
Height	1.73 in (4.4 cm)
Width	17.52 in (44.5 cm)
Depth	4.25 in (10.8 cm)
Net Weight	5.00 lb(US) (2.27 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Horizontal

Input

Line Rated Current	16 A
Permissible voltage	200...240 V

Input current limits	20 A
Load Capacity	3680 VA
Input Frequency	50/60 Hz

Output

Number of power socket outlets	8 IEC 60320 C13
--------------------------------	-----------------

Conformance

Product Certifications	cUL Listed CE CSA GOST IRAM MIC UL Listed VDE VCCI
------------------------	--

Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 UL 60950
-----------	--

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
---------------------------------------	-------------------------

Relative Humidity	0...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
-------------------------------------	----------------------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0...50000 ft (0.00...15240.00 m)
------------------	----------------------------------

Ordering and shipping details

GTIN	731304210818
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	2.76 in (7 cm)
------------------	----------------

Package 1 Width	19.13 in (48.6 cm)
-----------------	--------------------

Package 1 Length	13.50 in (34.3 cm)
------------------	--------------------

Package 1 Weight	7.59 lb(US) (3.443 kg)
------------------	------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Lead free	Yes
-----------	-----

Mercury free	Yes
--------------	-----

RoHS exemption information	Yes
----------------------------	---------------------

Environmental Disclosure	Product Environmental Profile
--------------------------	---


Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Recommended replacement(s)

AP7921 is replaced by:

1x		APC NetShelter Switched Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, x8 C13 outlets, C20 cord AP7921B
----	---	--