

Yealink DECT Repeater RT30

Yealink DECT repeater RT30, designed in accordance with Digital Enhanced Cordless Telecommunication (DECT) standard, is characterized by easy installation and a user friendly display concept. The repeater can be deployed to extend the DECT radio coverage of Yealink W60B/W70B base station significantly in all directions, and when working with W60B/W70B, it supports two RT30 cascaded. Clear LED indicators are used to distinguish different DECT statuses. What's more, its elegant design and easy installation are typically suitable to be used in the ambiance of modern business environments.

Key Features and Benefits

- Compatible with DECT CAT-iq 2.0
- Compatible with Yealink W60B/W70B/W52 DECT IP Base Station
- Up to 6 repeaters per base station
- Star connection
- Up to 2 repeaters can be arranged in cascade
- Auto association
- HD voice
- Plug & play setup
- Clear status LED display
- Elegant design
- Wall mountable



General Features

- Standards: DECT CAT-iq 2.0
- Extending the DECT coverage
- Supports automatic handover of calls between RT30
- Up to 4 simultaneous calls per repeater
- Up to 6 repeaters per base station
- Up to 4 repeaters can be arranged in cascade (only when connected to W60B/W70B)
- Auto association
- Base Link Reset
- LED Display
 - LED 1 Power On
 - LED 2 DECT Link
 - LED 3 Active Relay
- Compatible with Yealink W60B (version 77.81.0.35 or later)
- Compatible with Yealink W52 Base Station (version 25.81.0.10 or later)

- Compatible with Yealink W70B (version 146.85.0.15 or later)

Frequency/Coverage

- Indoor range up to 50 m (In ideal conditions)
- Outdoor range up to 300 m (In clear view and ideal conditions)
- 2 internal QWL omnidirectional antennas
- Modulation: GFSK
- Radio frequency range: 1880 MHz to 1900 MHz (EU), 1920 MHz to 1930 MHz (US)
- Transmission power: Average 10mW
- RX sensitivity: typ. -91dBm

Physical Features

- Desktop or wall mountable
- Power supply: AC 100-240V Input and DC 5V/600mA Output
- Dimension (W*H*T): 130 mm x 100 mm x 25.1 mm


Package Features

- Package content:
 - RT30
 - USB Cable
 - Power Adapter
 - User Guide
- Qty/CNT: 10 PCS
- Giftbox size: 174 mm*180 mm*63 mm
- Carton meas: 375 mm*336 mm*187 mm
- N.W: 3.2 kg
- G.W: 3.7 kg

Compliance



IC: 10741A-RT30





About Yealink

Yealink (Stock Code: 300628) is a global brand that specializes in video conferencing, voice communications and collaboration solutions with best-in-class quality, innovative technology and user-friendly experience. As one of the best providers in more than 140 countries and regions, Yealink ranks No.1 in the global market share of SIP phone shipments (Global IP Desktop Phone Growth Excellence Leadership Award Report, Frost & Sullivan, 2019).

Copyright

Copyright © 2022 YEALINK(XIAMEN) NETWORK TECHNOLOGY CO., LTD.

Copyright © 2022 Yealink(Xiamen) Network Technology CO., LTD. All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Yealink(Xiamen) Network Technology CO., LTD.

Technical Support

Visit Yealink WIKI (<http://support.yealink.com/>) for firmware downloads, product documents, FAQ, and more. For better service, we sincerely recommend you to use Yealink Ticketing system (<https://ticket.yealink.com>) to submit all your technical issues.



YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.
Web: www.yealink.com
Addr: No.1 Ling-Xia North Road, High Tech Park,
Huli District, Xiamen, Fujian, P.R. China
Copyright©2022Yealink Inc. All right reserved.